



Trowelable Crack Filler

DESCRIPTION:

GemSeal® Trowelable Crack Filler is a premium asphalt emulsion based heavy bodied crack filler, which can be easily applied to blacktop pavement defects such as dips, holes and cracks up to 1 1/2" wide. Fills and seals cracks and voids in pavement surfaces, to prevent damaging effects of water penetration and improves overall pavement appearance.

FEATURES:

- Can be used directly from the container
- Adheres tightly to sides of properly prepared cracks and joints to create a waterproof seal
- Helps keep out moisture which reduces pavement break-up caused by freeze/thaw action
- Improves surface appearance by eliminating dirt trapping cracks

CURING TIME:

The surface will usually dry in 4 hours, but weather and thickness may slow drying. Curing to full depth may take 5-7 days. Wait 48 hours before sealcoating over repairs.

PHYSICAL PROPERTIES:

Color - Black
Weight Per Gallon - Approximately 11 lbs.
Solids Content - 75-80%

USES:

To fill and seal cracks up to 1/2 inch wide, in blacktop and concrete surfaces such as walls, driveways, and parking lots. GemSeal Trowelable Crack Filler may be used to fill voids left by deterioration of the expansion joint material used between concrete slabs.

STORAGE:

Store in a cool, dry area. Avoid freezing. Product is no longer useful after freezing.

PREPARATION:

Clean all dirt, dust and loose materials from cracks with a stiff broom, water stream, and/or compressed air. Dampen the crack. Allow free standing water to dissipate before making application.

CLEAN-UP:

Clean tools with water immediately after use. Filler remaining on tools may be removed with mineral spirits.

INSTRUCTIONS FOR USE:

For best results, apply in dry warm weather. Do not apply when rain is forecasted within 48 hours or when the ambient air temperature is expected to fall below 50°F (10°C).

SERVICE:

Timely service is available within a 300 mile radius of our manufacturing facilities.

APPLICATION:

One gallon fills approximately 12 ft. of 1 1/2" wide x 1" deep cracks. Apply GemSeal Trowelable Crack Filler with cement trowel or putty knife, by pressing material into crevices to improve bond. Curing time will vary with thickness of application. Do not apply more than 1 1/2" deep in cracks or holes. Do not overfill. If possible, keep traffic off filled areas during curing period or sprinkle sand over filled areas to prevent tracking.



Trowelable Crack Filler

CAUTION:

HARMFUL IF SWALLOWED. Contact with any part of the body may cause skin irritation. Wash off with water immediately. Wearing gloves is recommended. KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING. Contains Asphalt CAS #8052-42-4

MANUFACTURING & CUSTOMER SERVICE:

Call (866) 264-8273 to find the nearest GemSeal location to purchase Trowelable Crack Filler.

GemSeal Pavement Products
Corporate Headquarters:
3700 Arco Corporate Drive, Suite 425
Charlotte, NC 28273

GemSeal Pavement Products warrants that for a period of one (1) year from date of purchase this product shall be free from manufacturing defects and shall meet or exceed performance standards listed in the technical data sheet for the product at the time of sale, if used as directed and within the stated shelf life. This Limited Warranty applies only if the product is stored, used, and applied over a properly prepared substrate in strict accordance with applicable specifications and instructions issued by GemSeal Pavement Products. The Limited Warranty will not apply if the product is altered, modified, or misused after it has left the control of GemSeal Pavement Products. GemSeal Pavement Products will not be responsible for defects caused by factors beyond its control, including but not limited to workmanship, application equipment, weather, acts of God, structural failure, condition or movement of substrate, improper additives, poor drainage, ponded water, improper maintenance, damage from snow removal equipment, and normal wear and tear. GemSeal Pavement Products does not warrant that the product or any method of use or application would be suitable for any particular site conditions.

All warranty claims must be submitted in writing, with proof of purchase, to the following address: 3700 Arco Corporate Drive, Suite 425, Charlotte, NC 28273. Unused portions of product must be returned upon request. Replacement of defective product or, at GemSeal Pavement Products' option, refund of the purchase price of defective product shall be the buyer's sole remedy under this Limited Warranty. In no event shall GemSeal Pavement Products be liable for any damages in excess of the purchase price of the defective product. This Limited Warranty does not cover labor costs for product application, replacement, or repair. GEMSEAL PAVEMENT PRODUCTS SHALL IN NO EVENT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, OR SPECIAL DAMAGES, INCLUDING BUT NOT LIMITED TO DAMAGES FOR LOST SALES OR PROFITS, BUSINESS INTERRUPTION, DELAYS, PHYSICAL DAMAGE TO OTHER MATERIALS OR PROPERTY, OR LOSS OF USE OF PROPERTY.

THIS LIMITED WARRANTY IS PROVIDED IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. GEMSEAL PAVEMENT PRODUCTS EXPRESSLY DISCLAIMS ANY OTHER WARRANTIES, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No modification or extension of this Limited Warranty shall be valid unless given in writing and signed by an authorized officer of GemSeal Pavement Products. Sales personnel and product distributors are not authorized to modify or extend this Limited Warranty.